

Important: Always disconnect the power before installing or replacing bulb and before cleaning or other maintenance.

This light should be installed by a licensed electrician

LAMP INSTALLATION AND ASSEMBLY

1. Shut off power to the outlet box. (fig. A)
2. Attach the mounting plate to the outlet box, secure with outlet box screws.
3. Determine the height at which the fixture is to be hung. Unscrew the cord lock screws, set the adjustable cords to the desired length and, if necessary, cut cords to length plus six inches. Tighten the cord lock screws with a screwdriver to prevent slippage. (Fig. B)
4. Make appropriate electrical connections using wire nuts:
 - a. Connect the fixture's live wire (black) to the live outlet box wire.
 - b. Connect the fixture's neutral wire (white) to the neutral outlet box wire.
 - c. Connect fixture's ground wire (green or uncoated) to the ground outlet box wire. If no ground is present in outlet box, connect fixture's ground wire to the mounting plate using the green screw (included).
 - d. Carefully place connections in outlet box.
5. Attach canopy to mounting plate, secure with finial.
6. Install 60W medium base bulbs. (not included)
7. Screw the mesh shades to threaded sockets.
8. Restore power to the fixture.

CARE INSTRUCTIONS

Dusting — Use a clean, dry cloth.

Cleaning — To protect the finish, avoid any harsh abrasives or chemicals.

